



global solutions :
local support™

Connector Adapters 100 to 5825 MHz Operation

The adapter connectors offered by Laird Technologies are used to adapt between various popular connector types. They are a less expensive alternative and lower loss than using custom pigtail cables. They have a high quality nickel plated body and contacts are gold plated for stable performance over time. Their design includes a knurled body for easier installation. Custom adapters are available for OEM customers.

Features and Benefits:

- Gold plated contacts
- Nickel body
- 0.1db max insertion loss
- VSWR better than 1.2:1
- N male connector converts N female connectors to various popular connector types

Applications

- WiFi / WLAN systems
- 802.11 a/b/g
- Base station and client systems

For sales information:

Telephone 801-572-3024

E-Mail sales@pacwireless.com

or visit: www.pacwireless.com



Specifications

Parameter	Min	Typ	Max	Units
Frequency Range	100		5825	MHz
Insertion Loss			.1	dB
VSWR		1.2:1		
Impedence		50		OHM
Input Power			50	W
Weight		1.4(40)		oz. (g)
Dimensions	1.5" x 0.75" dia (38 x 19)			in. (mm)

System Ordering:

AD-NM-SMAF	N Male –SMA Female Adapter
AD-NM-RPSMAM	N Male – RPSMA Male Adapter
AD-NM-RPSMAF	N Male – RPSMA Female Adapter
AD-NM-RPTNCM	N Male – RPTNC Male Adapter
AD-NM-UHFF	N Male – UHF Female Adapter
AD-RSMAF-RTNCM	RP SMA Female to RP TNC Male
AD-NM-NM	N Male to N Male Coupler
AD-NF-NF	N Female to N Female Barrel Adapter
AD-NM-RPTNCF	N Male to RP TNC Female
AD-NF-RPTNCM	N Female to RP TNC Male
AD-NF-RPSMAM	N Female to RP SMA Male
AD-MCX-RPSMAF	MCX to RP SMA Female
AD-NFB-SMAF	N Fem Bulkhead to SMA Female

Connector Adapters




N Male to
RPSMA Male




N Male to
RPSMA Female



N Male to
RPTNC Male



N Female Bulkhead to
SMA Female



MCX to
RPSMA Female

Notes:

- All shipments F.O.B. Schaumburg, IL 60173
- All antennas carry a 2 Year Warranty

Any information furnished by Laird Technologies and its agents is believed to be accurate and reliable. Responsibility for the use and application of Laird Technologies materials rests with the end user since Laird Technologies and its agents cannot be aware of all potential uses. Laird Technologies makes no warranties as to the fitness, merchantability, or suitability of any Laird Technologies materials or products for any specific or general uses. Laird Technologies shall not be liable for incidental or consequential damages of any kind. All Laird Technologies products are sold pursuant to the Laird Technologies domestic terms and conditions of sale in effect from time to time, a copy of which will be furnished upon request.

Specifications subject to change without notice.

