











LigoWave		Proxim	Redline		Cambium networks		Infinet	Radwin	
									
PTP UNITY	PTP PRO	Tsunami QB825	RDL-2000	RDL-3000 Enterprise	PTP 250	PTP 650	Infinet 2x2 PRO	2000 C	2000 C Plus

## Hardware

Operating frequency, GHz	4.8-6.3	4.8-6.3	5.1-5.9	4.8-6.0	4.9-5.8	5.4-5.8	4.9-6.05	4.9-6.0	4.9-6.0	4.9-6.0
Max transmit power, dBm	28	28	26	22	22	22	27	23	25	25
GE interface	2	1	1	0	1	1	2	1	1	1
Power consumption, W	12	8	15	7	35	35	30	30	15	15
OLED screen	Yes	Yes	No	No	No	No	No	No	No	No

## Software

Max speed, Mbps	220	220	100	270	100	256	450	270	200	250
Spectrum analyser	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
QoS	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
1+1 (failover mode)	Yes	No	No	Yes	Yes	No	No	No	No	No
2+0 (bonding mode)	Yes	No	No	No	No	No	No	No	No	No
Dual firmware image	Yes	Yes	No	No	No	No	No	No	No	No
Web based GUI	Yes	Yes	Yes	No	Yes	Yes	Yes	Yes	No	No
High-contrast mode in GUI	Yes	Yes	No	No	No	No	No	No	No	No
NMS	Yes	Yes	Yes	Yes	Yes	Yes	Yes	No	Yes	Yes
3rd party equipment monitoring on NMS	Yes	Yes	No	Yes	Yes	Yes	Yes	No	Yes	Yes
Mobile NMS version	Yes	Yes	No	No	No	No	No	No	No	No

## ROI

Link price, USD	1500	1300	1800	6000	3600	5000	5400	6000	6300	5000
1 Mbps price, USD	6.82	6.5	18	22.22	36	19.53	12	22.22	31.5	20