



Smart Technology. Delivered.

PDM245115H 4-Port Directional H/V MIMO Antenna



2.4-2.5 & 5.15-5.9 GHz 14 dBi 4-PORT DIRECTIONAL H/V MIMO ANTENNA

Laird's PDM245115H antenna is a 4-port directional antenna for use in 802.11n MIMO applications. Designed for low side lobe and front-to-back performance, the antenna is an excellent choice for high density WiFi applications where adjacent antenna interference is of concern. Equipped with two Vertically polarized ports and two Horizontally polarized ports, the antenna takes advantage of both polarization and spatial separation to mitigate multipath issues.

Enclosed in a compact/low profile Polycarbonate Radome and equipped with an articulating arm that can be affixed to a mast or anchored directly to a vertical surface, the antenna can be oriented to take full advantage of the antenna's directionality. Uniform and symmetrical radiation patterns provide high-level signal density into defined coverage zones. This antenna will greatly enhance the performance of 802.11n systems where physical obstructions are anticipated. The dual band frequency coverage means that a single type of antenna can be deployed with any MIMO radio in the 2.4-2.5 GHz and 5.15-5.9 GHz bands.

FEATURES

- 802.11n MIMO
- Wide band 2.4-2.5 GHz and 5.15-5.9 GHz performance
- Both Vertically and Horizontally polarized radiating elements in a single solution
- Equitable for both indoor and outdoor solution
- Low Profile
- Multipath mitigation
- Lower adjacent antenna interference
- Frequency diplexed dual polarized radiators

MARKETS

- High Density WiFi
- Stadiums, Arenas, Convention Centers
- Transport Terminals
- Campuses
- Outdoor Networks

SPECIFICATIONS

| ELECTRICAL | | |
|-------------------|---------------|--|
| Model Number | PDM245115H | |
| Frequency | 2400-2500 MHz | 5150-5900 MHz |
| Peak Gain | 14.0 dBi | 14.5 dBi |
| Nominal Impedance | 50Ω | |
| VSWR (H,V) | <1.6:1 | <2.0:1 (5150-5700 MHz) <1.5:1 (5700-5900 MHz) |

Americas: +1.847 839.6925
IAS-AmericasSales@lairdtech.com

Europe: +44.1628.858941
IAS-EUSales@lairdtech.com

Asia:
IAS-AsiaSales@lairdtech.com


Middle East & Affrica: +44.1628.858941
IAS-MEASales@lairdtech.com

www.lairdtech.com


| ELECTRICAL | | |
|---|--|--------|
| Azimuth Co-Polar First Sidelobe | -20 dB | -20 dB |
| Elevation Co-Polar First Sidelobe | -10 dB | -15 dB |
| F/B Ratio | 35 dB | |
| Azimuth Plane 3-dB Beamwidth (Typ.) | 31° | 31° |
| Elevation Plane 3-dB Beamwidth (Typ.) | 33° | 27° |
| Power | 1 Watt | |
| RF Connector | Type N, Female (4x) | |
| Radome | Polycarbonate, White | |
| Operational Temperature | -40°C to +70°C | |
| Storage Temperature | -40°C to +85°C | |
| Dimensions | 507 x 368 x 21.1 mm (20 x 14.5 x 0.8 in) | |
| Weight (no brackets) | 2.3 kg (5.1 lbs) | |
| Water/Foreign Body Ingress | IP67 | |
| RoHS Compliance | Yes | |
| Standard for Safety: Fire and Smoke (Plenum)* | UL 2043 Certified | |
| Flammability Rating (Radome) | UL94V0 Materials | |

AZIMUTH PATTERNS: 2450 MHZ


AZIMUTH PATTERNS: 5550 MHZ




H-pol



V-pol




H-pol




V-pol

ELEVATION PATTERNS: 2450 MHZ


ELEVATION PATTERNS: 5550 MHZ




H-pol



V-pol



H-pol



V-pol

ANT-DS-PDM24511H 0716

Any information furnished by Laird Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird materials rests with the end user, since Laird and its agents cannot be aware of all potential uses. Laird makes no warranties as to the fitness, merchantability or suitability of any Laird materials or products for any specific or general uses. Laird shall not be liable for incidental or consequential damages of any kind. All Laird products are sold pursuant to the Laird Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2016 Laird Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Logo, and other marks are trade marks or registered trade marks of Laird Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird or any third party intellectual property rights.